

## Rotary Evaporator Enclosure

- Provides Laboratory Safety While Using a Rotary Evaporator



P5-24-ROTO



Operator



Particulate



Vapor



## CONTENTS:

Product Overview (p.2)

Specifications (p.3)

Warranty (p.4)

Get a Quote. 

## INTRODUCTION

In the laboratory, a rotary evaporator (rotovap) is employed to remove volatile solvents or isolate components of reaction mixtures by evaporation. This may be done following a separation or extraction process. During rotary evaporation, the solvent is removed under vacuum and is subsequently trapped by the condenser and collected.

Although a rotovap is designed to condense and collect evaporated solvents, the possibility exists for small amounts of volatiles to escape the apparatus, posing potential risks of chemical fume exposure, explosion or implosion. These applications warrant additional protection for laboratory personnel by placing the unit in a fume hood or enclosure, minimizing potential risks associated with inhalation of noxious fumes and guarding against injury from exploding or imploding glassware. Since safety is critical to a successful laboratory outcome, ensuring the correct equipment is in use is vital to that success.

These units provide containment for the rotovap while permitting operator access and visibility of the enclosed operation. From customizable Rotovap Enclosures to affordable ductless fume hoods, Air Science protects your personnel during rotary evaporation procedures.

## SAFETY CONSIDERATIONS

Use of a rotovap in a fume hood or enclosure minimizes the risk associated with hazardous fume inhalation and protects from injury resulting from exploding or imploding glassware. Necessary personal protective equipment includes lab coats, eye protection, close-toed shoes and appropriate gloves.

- Processes using solvents generating noxious vapors that may escape the unit should be conducted in a fume hood or enclosure.
- Explosion may occur when using chemicals or mixtures that can be explosive under certain conditions, creating the risk of the operator or others in the area being injured by projectile glass or chemical exposure. A fume hood with the sash lowered serves to reduce the risk of injuries.
- Implosion can occur if glassware being utilized carries an undetected deformity, causing failure once it is placed under vacuum pressure, resulting in the potential for injury. Operation in a fume hood provides operator protection, particularly when maintaining a lowered sash during applications.
- When performing a high temperature evaporation process requiring the use of a heated oil bath, setting up under a fume hood makes the process less likely to be disturbed or pose a burn injury risk to others in the area.
- In order to facilitate operation of a rotary evaporator under a fume hood, a diagonal set up is preferred since a vertical condenser may be too tall to fit in the fume hood.

## KEY BENEFITS

- The ductless Rotovap Custom Enclosure offers increased internal height.
- Features a spacious interior, customizable for a larger rotovap apparatus with a taller condenser column.
- Horizontal sliding or hinged door(s) provide greater access to the interior.
- Built-in air slots allow bypass when doors are closed, maximizing operator safety and process accessibility.



*P5-24-ROTO-DUCT shown with 6" duct collar for connecting to in-house ventilation system*

**CONTENTS:**

- Product Overview (p.2)
- Specifications (p.3)
- Warranty (p.4)

Get a Quote. 

MODEL	VOLTAGE	DIMENSIONS			WEIGHT (LBS/KG)	
		Internal Height	External (W x D x H)	Shipping (W x D x H)	Net	Ship
P5-24-ROTO-A	120V, 60Hz	38" / 965.2 mm	39" x 24" x 50" / 990.6 x 609.6 x 1270 mm	50" x 40" x 48" / 1270 x 1016 x 1219.2 mm	250 / 113.4	300 / 136.1
P5-24-ROTO-G	230V, 50Hz	38" / 965.2 mm	39" x 24" x 50" / 990.6 x 609.6 x 1270 mm	50" x 40" x 48" / 1270 x 1016 x 1219.2 mm	250 / 113.4	300 / 136.1
P5-24-ROTO-DUCT	N/A	38" / 965.2 mm	39" x 24" x 44" / 990.6 x 609.6 x 1117.6 mm	50" x 40" x 48" / 1270 x 1016 x 1219.2 mm	180 / 81.6	230 / 104.3

**PRODUCT SPECIFICATIONS**

**Construction**

Finish	White epoxy coated steel frame and head unit. Clear sides and back panel.
Blower	EC blower.
Controls	Main On/Off.
Monitoring	Filter blockage alarm, standard.
Spill Tray	Black Polypropylene

P5-24-ROTO-DUCT supplied as enclosure only without any electronics.

**Efficiency**

P5-24-ROTO-A: Power Consumption* 120V, 60Hz	30 watt
P5-24-ROTO-G: Power Consumption* 230V, 50Hz	30 watt
Lighting	LED

\* Watts at calibrated airflow setpoint with GP Filter(s) and prefilter installed.

**OPTIONS & ACCESSORIES**

Safety Filter*	An additional carbon, HEPA or ULPA safety filter exceeding ANSI/ AIHA Z9.5 requirements can be installed after the main filter.	Safety filters for vapor or particulate protection are available for all models. Contact Air Science for ordering information.
Dwyer Airflow Meter	Continuous display of face velocity.	DWYER
Base Stand, Mobile, With Casters	Mobile base stand, fixed height, with locking casters.	CART-40
Bottom Shelf	Provides a lower storage shelf for mobile base stand.	CART-40-SHELF
Filter Saturation Alarm*	Electronic gas sensor that alerts the user when the filter becomes saturated and airflow is compromised.	FSA

Factory installed; specify when ordering. Available only on P5-24-ROTO-A and P5-24-ROTO-G.

**FILTER SUMMARY\***

Formula	Description
GP Plus!	The most widely used filter in the range, primarily for solvent, organic and alcohol removal.
HEPA/UPLA	Powders and particulates.

\* Other formulas may be available.

**MULTIPLEX FILTRATION SYSTEM, SUMMARY**

Application	Chemical	Chemical within Cleanroom
Secondary/Stacked Filter, Optional	C	H
Primary Filter	C	C
Pre-Filter	P	P

The system can be configured for the capture of acids, bases and particulates, such as biological aerosols, when paired with HEPA or ULPA filters.

**FILTER SPECIFICATIONS**

Primary Filter*	(1)
Pre-Filter*	(1)

\* For specific examples refer to Multiplex filtration system summary.



Through our partner company [Filtco Filters](#), Air Science is a single source supplier of all pre-filters, carbon filters and HEPA/ULPA filters used in our products.

<sup>1)</sup> Energy consumption disclosure is based on internal testing with primary filters during normal operation. Power consumption published is nominal and dependent on cabinet size.

**CONTENTS:**

- Product Overview (p.2)
- Specifications (p.3)
- Warranty (p.4)

Get a Quote. 

Warranty Info.

**WARRANTY**

This product is protected by the Air Science Legacy Limited Lifetime Warranty™.



For details visit the [Warranty section](#) of our website.



120 6th Street \ Fort Myers, FL 33907  
T. 239-489-0024 \ **Toll Free.** 800-306-0656 \ F. 800-306-0677  
airscience.com

**Air Science® Technologies Ltd.** \ United Kingdom  
T. 0151 526 2457 \ [airscience.com/UK](http://airscience.com/UK)

The information contained in this manual and the accompanying product are copyrighted and all rights are reserved by Air Science. Air Science reserves the right to make periodic minor design changes without obligation to notify any person or entity of such change.

