




High Clearance Ducted Fume Hoods / Enclosures

High clearance enclosures exhaust harmful fumes and particulates away from the operator's breathing zone when connected to inhouse vent system.

P20-XT-DUCT



CONTENTS:

- Product Overview (p.2)
- Design Features (p.3)
- Specifications (p.4)

INTRODUCTION

Air Science® Purair® DUCTED ADVANCED High Clearance Fume Hoods are designed to protect personnel from exposure to hazardous agents and toxic chemicals in various applications. These hoods are available in several standard sizes and offer higher internal height, larger widths, and greater usable depth than our standard DUCTED Basic unit. They are built for simplicity and feature a hinged folding front sash. Clear back, sides, and front panels allow ambient light into the chamber and provide users with an unobstructed view of contents. An open base allows easy placement over a variety of equipment or sinks. Optional worksurfaces are also available.

APPLICATIONS

This exterior-venting exhaust hood is typically used for applications with high volumes of volatile organic compounds and toxic chemicals, gases, or powders. Air Science Purair DUCTED ADVANCED High Clearance Fume Hoods utilize an external ducting system to provide an effective and economical tool for air quality enhancement in many commercial, chemical, medical, laboratory, and industrial applications.


Forensics \ Educational \ Microscopy \
Pharmaceutical \ Powder Weighing \ Sample Prep
Work \ Veterinary \ Dental



Deep into its second generation, Air Science embraces the diversity and cultural heritage of the founders and co-workers who are continuing a tradition of excellence. Air Science is a United States-based company with a domestic and global reach that is committed to adaptation, inclusion, and quality.

Air Science® USA LLC \ 120 6th Street, Fort Myers, FL 33907
T. 239-489-0024 \ airscience.com

Air Science® Technologies Ltd. \ United Kingdom
T. 0151 526 2457 \ airscience.com/UK



SELECTION

Purair DUCTED ADVANCED High Clearance Fume Hoods are available in 6 standard widths.

KEY FEATURES


- Chemical-resistant epoxy coated steel frame.
- 360 degree visibility.
- Protects the operator from fume hazards.



P15-XT-DUCT

AIRFLOW

Unlike a ductless fume hood, the Purair DUCTED ADVANCED High Clearance Fume Hood is installed in a fixed location and hard connected to the facility exhaust system to create a negative pressure work surface. Hazardous fumes and vapors generated on the work surface are exhausted to the outside. Air intake face velocity can be adjusted to provide the desired balance between conditioned room air conservation and the necessary volume of exhausted contaminated air.



Specifications are subject to change without notice or obligation on the part of Air Science. For questions, [contact Air Science](http://airscience.com).

CONTENTS:

- Product Overview (p.2)
- Design Features (p.3)
- Specifications (p.4)

PurairDUCTED ADVANCED
Ducted Fume Hoods / Enclosures

10 • 10XL • 15 • 20 • 25 • 30
DESIGN FEATURES

3



DESIGN FEATURES

- A. Optional Air Velometer:** An optional analog air velocity meter is positioned in the user's field of vision.
- B. Steel Support Frame:** The chemical-resistant epoxy coated steel frame adds mechanical strength.
- C. Hinged Front Sash:** When closed, the cabinet sash protects the contents from inadvertent external contact and better isolates the air within. The sash is easy to open and close.
- D. Optional Work Surface:** The internal work surface can be fitted with an optional polypropylene tray (available in white and black); see accessories.
- E. Pass Through Ports:** Cords and cables are safely routed into the cabinet through ports on the back.

ADDITIONAL FEATURES

360 Degree Visibility: Clear back and side panels allow ambient light into the chamber and provide users with an unobstructed view of contents.

! IMPORTANT NOTE: Ducting / fan not included with unit. End user is responsible for meeting exhaust ventilation regulations before venting fumes and should defer to the appropriate agency or agencies (federal, state, local) and / or contact a certified industrial hygienist or qualified safety professional to verify application suitability with this product.

CONTENTS:

Product Overview (p.2)


Design Features (p.3)

● Specifications (p.4)

PurairDUCTED ADVANCED

Ducted Fume Hoods / Enclosures

10 • 10XL • 15 • 20 • 25 • 30
SPECIFICATIONS



MODEL	DIMENSIONS				WEIGHT (LBS/KG)		
	Metal Construction	Internal Height	External (W x D x H)	Exhaust Collar / Duct Spigot Size	Shipping (W x D x H)	Net	Ship
P10-XT-DUCT		38" / 965 mm	30" x 27.375" x 45" / 762 x 695 x 1143 mm	6" / 150mm	50" x 40" x 42" / 1270 x 1016 x 1067 mm	65 / 29	90 / 41
P10XL-XT-DUCT		38" / 965 mm	34" x 27.375" x 45" / 864 x 695 x 1143 mm	6" / 150mm	40" x 40" x 42" / 1016 x 1016 x 1067 mm	80 / 36	105 / 48
P15-XT-DUCT		38" / 965 mm	39" x 27.375" x 45" / 991 x 695 x 1143 mm	6" / 150mm	40" x 50" x 42" / 1016 x 1270 x 1067 mm	100 / 45	125 / 57
P20-XT-DUCT		38" / 965 mm	49" x 27.375" x 45" / 1245 x 695 x 1143 mm	(2) 6" / 150mm	55" x 60" x 42" / 1397 x 1524 x 1067 mm	115 / 52	165 / 75
P25-XT-DUCT		38" / 965 mm	59" x 27.375" x 45" / 1499 x 695 x 1143 mm	(2) 6" / 150mm	40" x 67" x 42" / 1016 x 1702 x 1067 mm	130 / 59	185 / 84
P30-XT-DUCT		38" / 965 mm	69" x 27.375" x 45" / 1753 x 695 x 1143 mm	(3) 6" / 150mm	40" x 80" x 42" / 1016 x 2032 x 1067 mm	145 / 66	195 / 88

TYPICAL AVERAGE AIRFLOW REQUIREMENT AT CONNECTION

Metal Construction	Face velocity (FPM)	Air Flow Required (CFM)	Face Velocity (m/sec)	Airflow Required (m³/hr)
P10-XT-DUCT	100	250	0.5	425
P10XL-XT-DUCT	100	283	0.5	480
P15-XT-DUCT	100	325	0.5	552
P20-XT-DUCT	100	400	0.5	679
P25-XT-DUCT	100	491	0.5	834
P30-XT-DUCT	100	575	0.5	973

OPTIONS & ACCESSORIES

		P10-XT-ENCL-DUCT	P10XL-XT-ENCL-DUCT	P15-XT-ENCL-DUCT	P20-XT-ENCL-DUCT	P25-XT-ENCL-DUCT	P30-XT-ENCL-DUCT
Dwyer Airflow Meter	Continuous display of face velocity.	DWYER	DWYER	DWYER	DWYER	DWYER	DWYER
Spill Tray (Polypropylene)	Removable for easy cleaning.	TRAY-P10	TRAY-P10XL	TRAY-P15	TRAY-P20	TRAY-P25	TRAY-P30

CONTENTS:

Product Overview (p.2)

Design Features (p.3)

● Specifications (p.4)

PurairDUCTED ADVANCED

Ducted Fume Hoods / Enclosures

10 • 10XL • 15 • 20 • 25 • 30
SPECIFICATIONS

5

WARRANTY

This product is protected by the Air Science Legacy Limited Lifetime Warranty™.



For details visit the [Warranty section](#) of our website.

STANDARDS & COMPLIANCE

Quality Management Systems	ISO 9001 : 2015
OSHA, Occupational Safety and Health Administration	OSHA Standard -29 CFR, Safety and Health Regulations for General Industry, 1910.1450: Occupational exposure to hazardous chemicals in laboratories. Part B, definition, laboratory type hood. This product may assist you with compliance or as part of your chemical hygiene plan. Please consult your Safety Officer and/or Industrial Hygienist.
Environment	ISO 14001: 2015 ENERGY STAR® Partner



120 6th Street \ Fort Myers, FL 33907
T. 239-489-0024 \ **Toll Free.** 800-306-0656 \ F. 800-306-0677
airscience.com

Air Science® Technologies Ltd. \ United Kingdom
T. 0151 526 2457 \ airscience.com/UK

The information contained in this manual and the accompanying product are copyrighted and all rights are reserved by Air Science. Air Science reserves the right to make periodic minor design changes without obligation to notify any person or entity of such change.

